



Medical-Grade Digital Video Recorder

UR-4MD

Designed for the mission-critical OR environment


Full HD 1920 × 1080 Video and photo recording Advanced
Reliability
w/ Fail-safe recording

DICOM Gateway* Modality Worklist support

3.5 inch Built-in LCD display Simultaneous recording USB & iHDD

Plug & Play Automatic configuration

* DICOM Gateway is an optional upgrade.



Key Features

- Crystal-clear, full-HD 1920 × 1080, video and photo recording
- Built-in 3.5-inch LCD display for live view / playback / navigation
- Auto signal detection and auto resolution setting
- Safe recording to iHDD, USB devices and network drive simultaneously
- Networking (FTP and CIFS) RJ45 10/100/1000 Ethernet
- Remote control via camera or foot-pedal¹
- Feeding patient data via keyboard or barcode¹
- PACS connectivity²: DICOM storage and MWL support*

USB flash drive, USB hard drive

3.5 inch, full-color

■ Medical standards Specifications

Storage and Display

Recordable devices

Built-in LCD display

¹Optional device(s) required. ²Upgrade available.

Product Overview

UR-4MD is TEAC's latest high-definition medical video recorder designed for quick setup and ease of use, yet includes a robust list of features and capabilities. With auto-sensing video connections and automatic video resolution detection, setup is quick and easy.

The front control panel allows users to intuitively record videos and photos in crystal-clear HD. A built-in hard drive is included for reliable recording and data back-up and users can also simultaneously record to USB memory and USB hard drives to archive, share and play back on other devices and locations. UR-4MD is also network capable. With an optional upgrade, DICOM integration is made easy.

Recording Times (for a 500 GB hard drive)

HD definition 1920 x 1080		
12 Mbit/s	18 Mbit/s	24 Mbit/s
90 hours	60 hours	45 hours
SD definition 640 × 480		
3D definition 640 x 400		
5 Mbit/s	8 Mbit/s	10 Mbit/s
180 hours	135 hours	100 hours
Times are approximate		

JR-4MD Digital Video Recorder



Front view



Rear view

Recording format (FAT32) Compression File format JPEG, DICOM Photo JPG, DCM Video MPEG-4 AVC/H.264 MOV Input/Output 3G/HD-SDI: 1080p/1080i/720p, SD-SDI: 480i/576i SDI (BNC) ×1 Innut/ DVI (Single Link) ×1 High-definition Video Output NTSC, PAL S-Video ×1 Composite (BNC) ×1 NTSC, PAL Output SDI Thru ×1 * SDI video output terminal used in common SDI (BNC) ×1 Input/ LINE Output Stereo mini jack ×1 Audio

500-GB internal hard drive (1 TB available as an optional upgrade)

Input Stereo mini jack ×1 MIC RJ-45 (10BASE-T / 100BASE-TX / 1000BASE-T) ×1 2 front connectors for recordable devices USB 2.0 Type A ×3 1 rear connector for optional accessories Other interfaces 1 rear connector for accessing the internal hard drive USB 2.0 Type B $\times 1$ (on UR-4MD) Stereo mini jack ×3 For external trigger General AC 100-240 V, 50/60 Hz Power supply Dimensions (W \times D \times H) Approx. 211 mm \times 235 mm \times 89 mm Weight Approx. 2.6 kg UL 60601-2003, CE, IEC 60601-1, CSA 60601-1, EN 60601-1 Safety Certifications IEC 60601-1-2, EN 60601-1-2, ICES-003, FCC Class B

Blu-ray™ Disc, Blu-ray™ and the Blu-ray™ Disc logo are trademarks of Blu-ray™ Disc Association. Other company names, product names and logos in this document are the trademarks or registered trademarks of their respective owners. Features and specifications are subject to change without notice.

TEAC UR-4MD, Power cords, Cable clamp, Owner's manuals

Remote control unit, Foot-switch, Keyboard, Barcode/Card Reader

FDA Class 1, ANVISA, RoHS, CCC

TEAC EUROPE GmbH

Bahnstrasse 12, 65205 Wiesbaden-Erbenheim

Germany

Category

What's in the box Optional accessories

Tel.: +49 611-7158-349 Email: info@teac.eu

Fax: +49 611-7158-392 https://teac.eu/en/